

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
<b>APPROACHES TO NEW YORK - NANTUCKET SHOALS TO FIVE FATHOM BANK (Chart 12300)</b>							
630 15985	<b>Buzzards Bay Entrance Light</b>	41 23 48 N 71 02 01 W	<b>Fl W</b> 2.5s	67	17	Tower on red square on 3 red piles with large tube in center, worded BUZZARDS on sides.	Emergency light of reduced intensity when main light is extinguished. RACON: B(-•••). HORN: 2 blasts ev 30s (2s bl-2s si-2s bl-24s si).
		*					41/00
4030	<i>Rockland Dumping Ground Lighted Buoy DG</i>	44 07 10 N 69 00 06 W	<b>Fl Y</b> 4s	5		Yellow.	
		*					41/00
4120	<i>West Penobscot Bay Entrance Lighted Gong Buoy PB</i>	44 05 54 N 69 00 12 W	<b>Mo (A) W</b>		6	Red and white stripes with red spherical topmark.	
		*					41/00
15985 630	<b>Buzzards Bay Entrance Light</b>	41 23 48 N 71 02 01 W	<b>Fl W</b> 2.5s	67	17	Tower on red square on 3 red piles with large red tube in center, worded BUZZARDS on sides.	Emergency light of reduced intensity when main light is extinguished. RACON: B(-•••). HORN: 2 blasts ev 30s (2s bl-2s si-2s bl-24s si).
		*					41/00
19470	Nebraska Shoal Buoy 2NS	41 20 59 N 71 34 30 W				Red nun.	
		*					41/00
21948	NEW LONDON HARBOR LEADING LIGHT	41 21 47 N 72 05 14 W	<b>Oc R</b> 4s	36		On southeast bridge abutment of railroad bridge.	Shows red from 353° to 356°. Higher intensity on 354.5°.
		*			*		* 41/00
<b>CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2000</b>							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2190	- Buoy C					Yellow nun.	
						*	41/00
4150	KINKORA UPPER RANGE REAR LIGHT 120 yards, 050° from front light.		<b>Iso G</b> 6s	44		KRW on skeleton tower.	Visible on range line only.
	*						41/00
*16757	- Buoy 9					Green can.	Private aid.
							41/00
24650	- Warning Daybeacon A						<i>Remove from list.</i>
							* 41/00

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceeding the station number.

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
34335	- Buoy 3A	34 59 44 N 76 12 18 W				Green can.	
		*					41/00
*34341	- Buoy 4A					Red nun.	
							41/00
*34349	- Buoy 5A					Green can.	
							41/00
34350	- Daybeacon 5B	34 59 12 N 76 12 30 W				SG on pile.	
	*						41/00
	<b>Bradley Creek</b>						
39621.1	- Daybeacon 1	34 12 24 N 77 49 13 W				SG on pile.	Private aid.
		*					41/00
*40011	DEEP POINT MARINA LIGHT 1	33 55 46 N 77 59 40 W	FI G 2s	12		SG on pile.	Private aid.
							41/00
*40013	DEEP POINT MARINA LIGHT 2	33 55 47 N 77 59 38 W	FI R 2s	12		TR on pile.	Private aid.
							41/00
CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*1890.5	- Channel Lighted Buoy 5A	33 11 30 N 79 08 34 W	FI G 4s		4	Green.	
							41/00
*1895.5	- Channel Lighted Buoy 6A	33 11 37 N 79 08 34 W	FI R 4s		4	Red.	
							41/00
7115	ST. JOHNS BAR CUT RANGE FRONT LIGHT	30 24 14 N 81 25 40 W	Q W	19		KRW on tower on piles.	Visible 2° each side of rangeline.
		*					41/00
*9540.5	- Buoy 7A					Green can.	
							41/00
22600	- RANGE FRONT LIGHT	27 41 50 N 82 32 50 W	Q W	17		KRW on piles.	Visible 2° each side of rangeline. Lighted throughout 24 hours.
		*	*	*		*	* 41/00

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceeding the station number.

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*22600.5	- RANGE FRONT PASSING LIGHT	27 41 50 N 82 32 50 W	<b>FI W 4s</b>	17	5	On same structure as Cut C Channel Range Front Light.	Visible all around.
							41/00
22605	- RANGE REAR LIGHT 1,790 yards, 061.2° from front light.		<b>Iso W 6s</b>	59		KRW on skeleton tower on piles.	Visible 2° each side of rangeline. Lighted throughout 24 hours.
			*			*	* 41/00
*22605.5	- RANGE REAR PASSING LIGHT	27 42 12 N 82 32 16 W	<b>FI W 4s</b>	20	5	On same structure as Cut C Channel Range Rear Light.	Visible all around.
							41/00
22760	- RANGE FRONT LIGHT	27 45 48 N 82 31 14 W	<b>Q W</b>	15		KGB on small house on piles.	Visible all around; higher intensity on rangeline. Lighted throughout 24 hours.
		*	*	*		*	* 41/00
*22760.5	- RANGE FRONT PASSING LIGHT	27 45 48 N 82 31 14 W	<b>FI W 4s</b>	17	5	On same structure as Cut E Channel Range Front Light.	Visible all around.
							41/00
22765	- RANGE REAR LIGHT 1,271 yards, 017.9° from front light.		<b>Iso W 6s</b>	50		KGB on skeleton tower on piles.	Visible all around; higher intensity on rangeline. Lighted throughout 24 hours.
			*	*		*	* 41/00
*22765.5	- RANGE REAR PASSING LIGHT	27 46 25 N 82 31 01 W	<b>FI W 4s</b>	20	5	On same structure as Cut E Channel Range Rear Light.	Visible all around.
							41/00
*27630.5	- Daybeacon 27					SG on pile.	Private aid.
							41/00
*27725.5	- Daybeacon 49					SG on pile.	Private aid.
							41/00
*27790.5	- Daybeacon 69					SG on pile.	Private aid.
							41/00
*27805.5	- Daybeacon 73					SG on pile.	Private aid.
							41/00
*27850.5	- Daybeacon 85					SG on pile.	Private aid.
							41/00
*27855.5	- Daybeacon 87					SG on pile.	Private aid.
							41/00
*27890.5	- Daybeacon 97					SG on pile.	Private aid.
							41/00

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceeding the station number.

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*27925.2	- Daybeacon 107					SG on pile.	Private aid.  41/00
*27925.4	- Daybeacon 108					TR on pile.	Private aid.  41/00
*27925.6	- Daybeacon 110					TR on pile.	Private aid.  41/00
CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
13402	Alliance Anchorage Upper Daybeacon 65.8	29 43 35 N 89 59 47 W				NY on pile.	Ra ref.  41/00
		*					
14560	HONEYWELL CHEMICAL DOCK LIGHTS (2) LDB mile 186.8.		FI R 4s			On pier.	Private aids.  41/00
	*					*	
22605	- ENTRANCE CHANNEL RANGE A FRONT LIGHT	29 21 18 N 94 43 00 W	FI W 2.5s	20		On skeleton tower.	For upbound traffic. Lighted throughout 24 hours.  41/00
		*	*				
22700	- ENTRANE CHANNEL RANGE C FRONT LIGHT	29 20 30 N 94 46 57 W	Q G	35		KRW on skeleton tower on piles.	Visible 2° each side of rangeline.  41/00
		*					
22730	GALVESTON NORTH JETTY LIGHT WR2 Marks derelict wreck.	29 21 50 N 94 44 38 W	Q R	17	3	TR on pile.	  41/00
		*					
22790 34400	- LIGHT 2	29 20 14 N 94 46 35 W	Q R	17	3	TR-TY on dolphin.	Ra ref.  41/00
		*					
22795 34405	- LIGHT 3	29 19 47 N 94 46 28 W	FI G 2.5s	10	4	SG-SY on dolphin.	Ra ref.  41/00
		*					
22888	- LIGHT 28	29 22 40 N 94 48 19 W	FI R 2.5s	17	4	TR on pile.	  41/00
		*					
22910	- LIGHT 32	29 24 28 N 94 49 14 W	FI R 2.5s	17	4	TR on pile.	Ra ref.  41/00
		*					

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceeding the station number.

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
22930	- LIGHT 36 120 feet outside channel limit.	29 25 05 N 94 49 33 W	<b>FI R</b> 6s	17	4	TR on pile.	Ra ref.
		*					41/00
22945	- LIGHT 38	29 25 41 N 94 49 51 W	<b>FI R</b> 2.5s	17	4	TR on pile.	
		*					41/00
22960	- LIGHT 39	29 26 13 N 94 50 19 W	<b>FI (2) G</b> 6s	17	4	SG on pile.	Ra ref.
		*					41/00
<b>Houston Ship Channel</b>							
23985	- LIGHT 104	29 42 22 N 95 01 02 W	<b>FI R</b> 2.5s	17	4	TR on pile.	
		*					41/00
24000	- LIGHT 108	29 42 42 N 95 01 09 W	<b>FI R</b> 6s	17	4	TR on pile.	
		*					41/00
24035	- LIGHT 111	29 43 17 N 95 01 20 W	<b>FI G</b> 2.5s	17	4	SG on pile.	Ra ref.
		*					41/00
24210	CROSSOVER INBOUND RANGE FRONT LIGHT	29 45 19 N 95 03 56 W	<b>Q R</b>	40		KRW on skeleton tower on piles. On same structure as Lynchburg Outbound Range Front Light.	For upbound traffic. Visible 2° each side of rangeline.
		*					41/00
24220	CROSSOVER OUTBOUND RANGE FRONT LIGHT	29 44 26 N 95 03 41 W	<b>Q G</b>	35		KRW on skeleton tower on piles. On same structure as Upper Peggy's Lake Inbound Range Front Light.	For downbound traffic. Visible all around; higher intensity on rangeline.
		*					41/00
24240	UPPER CROSSOVER INBOUND RANGE FRONT LIGHT	29 45 43 N 95 04 24 W	<b>Q R</b>	30		KRW on skeleton tower on piles.	
		*	*	*			* 41/00
24530	Fidelity Island Daybeacon 2	29 43 39 N 95 15 27 W				TR on pile.	
		*					41/00
24555	- LIGHT 6	29 38 03 N 94 44 48 W	<b>FI R</b> 4s	17	3	TR on pile.	Ra ref.
		*					41/00
24565	- LIGHT 10	29 38 28 N 94 43 27 W	<b>FI R</b> 2.5s	17	3	TR on pile.	Ra ref.
		*					41/00

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceeding the station number.

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
<b>UPPER GALVESTON BAY (Chart 11327)</b>							
<b>Dickinson Bayou Channel</b>							
24895	- Daybeacon 1	29 28 03 N 94 51 32 W				SG on pile.	Ra ref.
		*					41/00
24900	- Daybeacon 2	29 28 00 N 94 52 45 W				TR on pile.	Ra ref.
		*					41/00
24910	- LIGHT 4	29 27 44 N 94 53 59 W	<b>FI R 4s</b>	17	4	TR on pile.	Ra ref.
		*					41/00
25045	EAGLE POINT WRECK LIGHT WR1	29 29 15 N 94 53 34 W	<b>Q G</b>	17	3	NB on dolphin.	
		*					41/00
<b>Clear Creek Channel</b>							
25065	- Daybeacon 1	29 33 06 N 94 59 32 W				SG on pile.	Ra ref.
		*					41/00
25070	- LIGHT 2 60 feet outside channel limit.	29 33 09 N 94 59 32 W	<b>FI R 6s</b>	30	4	TR on skeleton tower on piles.	HORN: 1 blast ev 10s (2s bl). Operates continuously from Nov. 1 to Apr. 30. Ra ref.
		*					41/00
25075	- Daybeacon 3	29 33 02 N 95 00 00 W				SG on pile.	Ra ref.
		*					41/00
25085	- Daybeacon 5	29 32 58 N 95 00 27 W				SG on pile.	Ra ref.
		*					41/00
25090	- LIGHT 6	29 33 01 N 95 00 36 W	<b>FI R 2.5s</b>	17	3	TR on pile.	Ra ref.
		*					41/00
25095	- Daybeacon 7	29 32 53 N 95 00 57 W				SG on pile.	Ra ref.
		*					41/00
25100	- LIGHT 8	29 32 56 N 95 00 57 W	<b>Q R</b>	17	3	TR on pile.	Ra ref.
		*					41/00
25125	- LIGHT 16	29 33 18 N 95 02 33 W	<b>FI R 4s</b>	17	3	TR on pile.	
		*					41/00

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceeding the station number.

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
25145	- LIGHT 20	29 33 17 N 95 03 39 W	<b>F I R</b> 4s	17	3	TR on pile.	
		*					41/00
25150	- LIGHT 23 50 feet outside channel limit.	29 33 08 N 95 04 11 W	<b>Q G</b>	17	4	SG on pile.	
		*					41/00
<b>Clear Lake Nasa Channel</b>							
25435	- Junction Daybeacon A	29 33 10 N 95 04 10 W				JR on pile.	
		*					41/00
25440	- Junction Daybeacon B	29 33 09 N 95 04 13 W				JR on pile.	
		*					41/00
25635	- LIGHT 10	28 56 24 N 95 17 58 W	<b>O c R</b> 4s	17	5	TR on pile.	
		*					41/00
25730	FREEPORT HARBOR LIGHT 21	28 55 55 N 95 19 39 W	<b>F I G</b> 2.5s	17	3	SG on pile.	
		*					41/00
31990	- Daybeacon 63	30 18 57 N 87 31 19 W				SG-SY on pile.	Ra ref.
		*					*
							41/00
34325	- LIGHT 13	29 19 39 N 94 50 49 W	<b>F I G</b> 2.5s	17	4	SG-SY on pile.	Ra ref.
		*					41/00
34355	- LIGHT 17	29 18 39 N 94 52 16 W	<b>F I G</b> 4s	17	5	SG-SY on pile.	Ra ref.
		*					41/00
34360	- LIGHT 18	29 18 42 N 94 52 20 W	<b>F I R</b> 4s	17	5	TR-TY on pile.	Ra ref.
		*					41/00
34400 22790	- LIGHT 2	29 20 14 N 94 46 35 W	<b>Q R</b>	17	3	TR-TY on dolphin.	Ra ref.
		*					41/00
34405 22795	- LIGHT 3	29 19 47 N 94 46 28 W	<b>F I G</b> 2.5s	10	4	SG-SY on dolphin.	Ra ref.
		*					41/00

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceeding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
34440	- LIGHT 2 150 feet outside channel limit.	29 18 40 N 94 49 51 W	FI R 4s	17	3	TR-TY on pile.	
		*					41/00
34475	- RANGE B FRONT LIGHT	29 18 32 N 94 52 41 W	Q R	17		KRW-I on pile structure. On same structure as Range C Front Light.	Visible all around; higher intensity on rangeline.
		*					41/00
34600	- RANGE C FRONT LIGHT	29 18 32 N 94 52 41 W	Q R	17		KRW-I on pile structure. On same structure as Range B Front Light.	For eastbound traffic. Visible all around higher intensity on rangeline.
		*					41/00
34905	- LIGHT 47	29 17 19 N 94 55 21 W	FI G 4s	17	4	SG-SY on pile.	
		*					41/00
34925	- RANGE F FRONT LIGHT	29 17 25 N 94 55 04 W	Q W	15		KRW-I on pile structure.	For eastbound traffic. Visible 2° each side of rangeline.
		*					41/00
35720	- LIGHT 8 60 feet outside channel limit.	28 30 48 N 96 18 12 W	FI R 4s	17	4	TR on pile.	Ra ref.
						*	41/00

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
365 4245	<b>Mile Rocks Light</b>	37 47 34 N 122 30 37 W	FI W 5s	49	15	White cassion with orange bands.	HORN: 1 blast ev 30s (2s bl). Operates continuously.
		*			*		41/00
4245 365	<b>Mile Rocks Light</b>	37 47 34 N 122 30 37 W	FI W 5s	49	15	White caisson with orange bands.	HORN: 1 blast ev 30s (2s bl). Operates continuously.
		*			*		41/00
6120	- MARINA NORTH ENTRANCE WEST LIGHT	38 06 37 N 122 16 21 W	FI G 2.5s	7		On post on breakwater.	Private aid.
	*	*	*			*	41/00
6125	- MARINA NORTH ENTRANCE EAST LIGHT	38 06 36 N 122 16 20 W	FI R 2.5s	7		On post on breakwater.	Private aid.
	*	*	*			*	41/00
6130	- MARINA CENTER ENTRANCE NORTH LIGHT	38 06 32 N 122 16 16 W	FI G 4s	7		On post on breakwater.	Private aid.
	*	*	*			*	41/00

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceeding the station number.



## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
6135	- MARINA CENTER ENTRANCE SOUTH LIGHT	38 06 32 N 122 16 16 W	FI R 4s	7		On post on breakwater.	Private aid.
	*	*	*			*	41/00
6136	- MARINA SOUTH ENTRANCE WEST LIGHT	38 06 24 N 122 16 06 W	FI G 6s	7		On post on breakwater.	Private aid.
	*		*	*		*	41/00
6137	- MARINA SOUTH ENTRANCE EAST LIGHT	38 06 23 N 122 16 03 W	FI R 6s	7		On post on breakwater.	Private aid.
	*	*	*	*		*	41/00
29568	- Danger Daybeacon	21 23 04 N 157 57 36 W		4		NW on structure.	Private aid.
		*					41/00
CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
3565	- LIGHT 8	42 09 06 N 80 04 53 W	FI R 4s	30 9	4	TR on post.	
		*					41/00
3570	- Junction Buoy M	42 09 06 N 80 04 55 W				Red with green band; nun.	
		*					41/00
12704	Bow Island Buoy 1	46 02 01 N 83 49 30 W				Green can.	
	*					*	41/00
14135	- Junction Lighted Buoy LR		FI (2+1) R 6s		4	Red with green band.	
							* 41/00
14635	Marquette Breakwater Outer Light		Oc W 4s (R sector)	36 11	W 15 R 12	White cylindrical tower with red band.	Red from 181° to 198°. HORN: 1 blast ev 15s (2s bl). Operates from May 1 to Oct. 20. Operates by keying the mike 5 times on VHF-FM Ch. 79.
							* 41/00
18635	- Entrance Buoy 1						Remove from list.
							* 41/00
20440	- DISPOSAL AREA LIGHT						Remove from list.
							* 41/00

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceeding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
22015	OCONTO HARBOR NORTH PIERHEAD LIGHT 2	44 53 54 N 87 49 18 W	<b>F R</b>	40 <b>12</b>	5	TR on pile.	Maintained from Apr. 15 to Nov. 1. Private aid.

\*

41/00

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceeding the station number.